

Data-Sheet USB-Ampel



- Super-bright LED traffic light with 3 light in red, yellow and green
- Contained in black plastic case 40 x 90 x 23 mm / IP30
- Every light is controlled independently
- Valid operating range -20° to +80° C
- ClewareControl to control display on other PC
- Application Program Interface for easy integration in user applications
- The control software [ClewareControl](#) for timed switching, [USBswitch](#) with a graphical user interface and [USBswitchCmd](#) for switching via command call is ready for [download](#).
- No driver installation needed with Windows® x86/x64 variants. (® Microsoft Windows is a registered trademark of the Microsoft Corporation.)
- Can also be used under different [Linux](#) support
- Application Program Interface for easy integration in user applications
- Use with LabView® possible
- RoHS, CE & EN60950 conform/ IP30
- For indoor use only.
- Multiple USB-Switches at a single PC controlled by unique the serial number
- Max. 440 mA power consumption
- USB cable length see cable length option
- **4 years warranty**
- Made in Germany
- Please find a detailed description here: [USB-Ampel](#)

Customs Tariff number: 85312020

Country of origin: Germany

Item details:

Version	EAN number	Weight/g	Length/mm	Height/mm	Width/mm
USB-Ampel	4251566201387	90	88	27	39
USB-Ampel L	4251566201394	120	88	27	39
USB-Ampel IP54	4251566201400	110	88	27	39
USB-Ampel IP54 L	4251566201417	140	88	27	39