

Data-Sheet USB-IO16



- 16 independant configurable IO channels
- potential connected - easy use with simple closing contacts
- Black plastic housing 45 x 90 x 23 mm
- 25 pin standard SubD plugor socket (see options)
- Valid temperature range -20° to +80° C
- Export of the states for Excel etc.(ClewareControl)
- Application Program Interface for easy integration in user applications
- The control software [ClewareControl](#) for timed switching, [USBswitch](#) with a graphical user interface and [USBswitchCmd](#) for switching via command call is ready for [download](#).
- Any contact may control up to 256 actions in ClewareControl, e.g. alarm sound, **email** or USB-Switch, SMS possible via the command line interface
- No driver installation needed with Windows® x86/x64 variants. (® Microsoft Windows is a registered trademark of the Microsoft Corporation.)
- Can also be used under different [Linux](#) support
- Application Program Interface for easy integration in user aplikations
- Use with LabView® possible
- For indoor use only.
- Multiple devices at a single PC controlled by unique the serial number
- Configurable power consumption (50 - 200 mA)
- USB cable length see cable length option
- 4 years warranty
- Made in Germany
- Please find more infos at: [USB-IO 16](#)
- Easy connection with the [IO16 connection set](#)

Customs Tariff number: 85365005

Country of origin: Germany

Item details:

Version	EAN number	Weight/g	Length/mm	Height/mm	Width/mm
USB-IO16	4251566201530	90	88	25	45
USB-IO16 L	4251566201554	120	88	25	45