

Data-Sheet USB-Switch 3,5



- PC-controlled switch for low voltage applications < 36 V
- comes with 3,5 mm mono jack or 2 pin plug sockets - see options
- switches 30V / 3A (max 100W) with an extrem reliable Finder®-Relais
- The control software ClewareControl for timed switching, USBswitch lies with a graphical user interface and USBswitchCmd for switching via command invocation for [download](#)
- Software included with the device: Control software [ClewareControl](#) for time controlled switching, [USBswitch](#) with a simple graphical user interface and [USBswitchCMD](#) for switch through a command line interface. Any switch could be controlled by programmed timer with up to 256 switch points
- No driver installation needed with Windows® Operating Systems since Windows® 2K (® Microsoft Windows is a registered trademark of the Microsoft Corporation.)
- Application Program Interface for easy integration in user applications
- [Linux](#) support available.
- RoHS, CE & EN60950 conform/ IP30
- About 120 mA power consumption when turned on
- For indoor use only
- Multiple USB-Switches at a single PC controlled by unique the serial number
- USB cable length see cable length option
- **4 years warranty**
- Made in Germany
- Please find more infos at: [USB-Switch NV](#)

Customs Tariff number: 85365019

Country of origin: Germany

Item details:

Version	EAN number	Weight/g	Length/mm	Height/mm	Width/mm
USB-Switch 3,5	4251566200946	180	95	52	63
USB-Switch 3,5 L	4251566200953	210	"	"	"