

## Data-Sheet USB-Alarm



- USB-controlled Piezo alarm
- about 85dB
- Frequency 2,3 kHz
- Black plastic housing about. 44 x 30 x 23 mm
- Operating temperature range -20° bis +80° C
- The control software [ClewareControl](#) for timed switching, [USBswitch](#) with a graphical user interface and [USBswitchCmd](#) for switching via command call is ready for [download](#).
- Multiple USB-Alarm at a single PC controlled by unique the serial number
- Control software [ClewareControl](#) enables this acoustic alarm to be turned on when the [USB-Temp](#) detect high temperature
- No driver installation needed with Windows® x86/x64 variants. (® Microsoft Windows is a registered trademark of the Microsoft Corporation.)
- Application Program Interface for easy integration in user applications
- Use with LabView® possible
- Can also be used under different [Linux](#) support
- RoHS, CE & EN60950 conform/ IP20
- About 50 mA power consumption when turned on
- USB cable length see cable length option
- For indoor use only
- **4 years warranty**
- Made in Germany

**Customs Tariff number: 85311095**

**Country of origin: Germany**

**Item details:**

<b>Version</b>	<b>EAN number</b>	<b>Weight/g</b>	<b>Length/mm</b>	<b>Height/mm</b>	<b>Width/mm</b>
USB-Alarm	4251566202384	60	58	22	30
USB-Alarm L	4251566202391	90	58	22	30