

Data-Sheet USB-SwitchC UK ++ M



- PC-controlled mains switch with Type G UK mains connectors
- **conductor and phase will be disconnected**
- Switches 240V / 13 A, max 3,000 W (single phase motor rating max. 550 W) using two extrem reliable Finder®-Relais
- **Automatic switch-off** when monitoring time (adjustable 1-100 seconds) is exceeded
- Multiple USB-Switches at a single PC controlled by the serial number
- Special version ATXX available which turns on with the PC
- The control software [ClewareControl](#) for timed switching, [USBswitch](#) lies with a graphical user interface and [USBswitchCmd](#) for switching via command invocation for [download](#)
- Software included with the device: Control software ClewareControl for time controlled switching, USBswitch with a simple graphical user interface and USBswitchCMD for switch through a command line interface. Any switch could be controlled by programmed timer with up to 256 switch points
- No driver installation needed with Windows® x86/x64 variants. (® Microsoft Windows is a registered trademark of the Microsoft Corporation.)
- Application Program Interface for easy integration in user applikations
- [Linux](#) support now available.
- Use with LabView® possible
- RoHS, CE & EN60950 conform/ IP20
- About 120 mA power consumption when turned on
- USB cable length see cable length option
- For indoor use only
- **4 years warranty**
- Made in Germany
- more info are available at [USB-Switch](#)

Customs Tariff number: 85369095

Country of origin: Germany

Item details:

Version	EAN number	Weight/g	Length/mm	Height/mm	Width/mm
USB-SwitchC UK ++ M	4251566201592	350	95	52	96
USB-SwitchC UK ++ M L	4251566201608	380	95	52	96