

Data-Sheet USB-MiniTrafficLight 360°



- USB mini traffic light allround visible
- Black housing, approx. 70 x 70 mm, device height 255 mm
- bore holes for mounting in the base foot
- Each color can be controlled separately in alternation
- Operating conditions: indoor, -0° bis +60° C
- The control software [ClewareControl](#) for timed switching, [USBswitch](#) with a graphical user interface and [USBswitchCmd](#) for switching via command call is ready for [download](#).
- Application Program Interface (DLL) for easy integration in user applications
- Easy indicator function using ClewareControl, e.g. temperature alarm
- No driver installation needed with Windows® x86/x64 variants. (® Microsoft Windows is a registered trademark of the Microsoft Corporation.)
- Can also be used under different [Linux](#) support
- Application Program Interface for easy integration in user applikations
- Use with LabView® possible
- RoHS, CE & EN60950 konform
- Multiple USB devices at a single PC controlled by unique serial number
- Max. power consumption 170 mA, typical 70 mA
- **4 Jahre warranty**

Customs Tariff number: 85312020

Country of origin: Germany

Item details:

Version	EAN number	Weight/g	Length/mm	Height/mm	Width/mm
USB TischAmpel 360°	4251566202674	315	70	255	70
USB TischAmpel 360° L	4251566202681	345	70	255	70